

75HP ROPS

ENGINE

ITL 4100 FL Diesel Engine Water Cooled 4Cylinder/3707cc Turbocharged 75 Hp @ 2200 RPM 278Nm Max Torque @1200 RPM Dual dry air cleaner with clogging sensor Upswept exhaust with silencer under hood 88 Lt fuel tank capacity

TRANSMISSION

Synchronised Shuttle Transmission 12 Forward gears + 12 Reverse gears Forward/Reverse LH Shuttle lever 35km/h Gearbox 4WD Mode - Mechanical lever engagement Front Axle Power steering Rear Diff Lock - Mechanical foot pedal Rear oil immersed brakes Mechanical hand brake

PTO

2 Speed Rear PTO 540 + 540 Economy Speed 540 @ 1938 engine rpm 540E @ 1646 engine rpm Mechanical lever engagement Mechanical selector lever

OPERATING AREA

Foldable rear mounted 2 Post ROPS Semi flat platform Rubber floor mat Front noise/mud deflectors Adjustable mechanical suspended seat Seat equipped with seatbelt Analogue dash with digital hour meter Ergonomic controls Sun Canopy

ELECTRICAL

12V -110Ah Battery 12V - 90 Amp Alternator Battery isolator switch 2 Bonnet headlights with Hi/lo beam 4 ROPS work lights Front park lights Front and rear indicators Rear brake and tail lights Rotary Beacon 7 Pin trailer socket

HYDRAULICS/3-POINT LINKAGE/HITCH

Open Centre Hydraulics Hydraulic Pump Capacity - 67 LPM Rear remotes - 2 sets Single/Double Acting Hydraulic Flow @ remote 44 LPM CAT 2 Rear 3-point linkage RH Position and Draft Levers Quick hitch hook ends 2500kg capacity Adjustable sway bars Swinging rear drawbar

WHEELS/DIMENSIONS/WEIGHTS

Radial Ag tyre and wheel package 280/85R24 Front tyres 420/85R30 Rear tyres Front dynamic steering fenders Rear wheel weights - 2 × 34kg Wheelbase - 2350mm Total length with loader - TBC Total width - TBC Total height - TBC Min ground clearance - TBC Front track - TBC Rear track - TBC Tractor weight - TBC

FRONT END LOADER

SOLIS/TITAN 8300 Level lift loader Single lever joystick and valve Electric diverter 3rd function 1.8mt 4in1 bucket SOLIS EASY Vision quick change EURO hitch Lift Height @ Bucket Pivot point - 3460mm Lift Height @ bottom of Bucket -3120mm Dump clearance - 2560mm Dump angle - 54 degrees Crowd angle @ ground level - 46 degrees Crowd angle @ full height - 48 degrees

