

H26 HST



26HP ROPS

ENGINE

Mitsubishi Stage V Diesel Engine Water Cooled with vertical overhead valve 3 Cylinder/1319 cc Naturally Aspirated 26 Hp @ 2500 RPM 76.3 Nm Max Torque Dry air cleaner with clogging sensor Downswept exhaust with silencer under hood 22 Lt fuel tank capacity

TRANSMISSION

2 Range Hydrostatic transmission Side by Side Hydrostatic Pedals Min Speed 3.18km/h Max Speed 21km/h Cruise Control 2WD + 4WD Modes - Mechanical Rear Diff Lock - Mechanical Rear oil immersed brakes Mechanical hand brake

PTO

2 Speed PTO Rear - 540 Speed Mid - 2100 Speed Electro hydraulic engagement Mechanical selector lever PTO safety switch

OPERATING AREA

Foldable rear mounted 2 Post ROPS Mono block mounted semi flat platform Rubber floor mat Adjustable deluxe mechanical suspended seat Seat equipped with Headrest, Armrests + seatbelt Analogue dash with digital hour meter Ergonomic controls

ELECTRICAL

12V -65Ah Battery 12V - 42 Amp Alternator Battery isolator switch 2 Bonnet headlights with Hi/lo beam Front park lights Front and rear Indicators Rear bake and tail lights Rear work light Rotary Beacon 7 Pin trailer socket

HYDRAULICS/3-POINT LINKAGE/HITCH

Open Centre Hydraulics Hydraulic Pump Capacity 16.5 LPM Rear remotes - 1 set CAT 1-N Rear 3-point linkage 600kg capacity Mechanical right-hand side lever control Adjustable sway bars Rear drawbar

WHEELS/DIMENSIONS/WEIGHTS

Galaxy Pro fixed wheel/tyre package 220/55R12 Front tyres 280/70R16 Rear tyres Wheelbase - 1590mm Total length with loader - 3850mm Total width - 1290mm Total height - 2280mm Min ground clearance - 190mm Front track - 950mm Rear track - 995mm Tractor weight fitted with loader - 1470kg

FRONT END LOADER

SOLIS/TITAN 3200 EH Level lift loader Integrated loader joystick and valve Electric diverter 3rd function 1.35mt 4in1 bucket SOLIS EASY Vision quick change EURO hitch Lift Height @ Bucket Pivot point - 2170mm Lift Height @ bottom of Bucket - 1950mm Dump clearance - 1635mm Dump angle - 45 degrees Crowd angle @ ground level - 43 degrees Crowd angle @ full height - 47 degrees ROL with No Ballast - 235kg ROL with 250kg ballast - 300kg

