

SPECIFICATIONS

Model		UT6070P	UT6570PC	UT6080P	UT6580PC
Engine		Diesel	Diesel	Diesel	Diesel
Model		4F243DTP-A	4F243DTP-A	4HT-TP2A	4HT-TP2A
Type		4Cyl., Water-cooled CRDI turbo charger engine			
Engine Gross Power	HP(kw)	66(49.2)	66(49.2)	75.1(56.0)	75.1(56.0)
Rated revolution	rpm	2600	2600	2600	2600
Total displacement	cc(cu in.)	2,435(148.6)	2,435(148.6)	2,435(148.6)	2,435(148.6)
Fuel tank	ℓ(us gal)	85(22.45)	95(25.1)	85(22.45)	95(25.1)
Drive Train					
Transmission		Power Shuttle Transmission	Power Shuttle Transmission	Power Shuttle Transmission	Power Shuttle Transmission
Main gear shift x range gear shift		4 X 6	4 X 6	4 X 6	4 X 6
No. of speeds		24 X 24	24 X 24	24 X 24	24 X 24
shuttle Type		Power Shuttle	Power Shuttle	Power Shuttle	Power Shuttle
Steering		Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering
Main Brake type		Wet Multi Disc	Wet Multi Disc	Wet Multi Disc	Wet Multi Disc
Main Clutch type		Hydro Multi Wet Disc Clutch	Hydro Multi Wet Disc Clutch	Hydro Multi Wet Disc Clutch	Hydro Multi Wet Disc Clutch
Mechanical differential lock		Rear Standard	Rear Standard	Rear Standard	Rear Standard
Hydraulic					
3 Point Lift Control Type		Position, Draft, Mixed Control	Position, Draft, Mixed Control	Position, Draft, Mixed Control	Position, Draft, Mixed Control
Total hydraulic flow	lpm(cc/rev)	67.6(26)	67.6(26)	72.8(28)	72.8(28)
Implement Pump	lpm(cc/rev)	41.6(16)	41.6(16)	41.6(16)	41.6(16)
Power steering pump	lpm(cc/rev)	26(10)	26(10)	31.2(12)	31.2(12)
3-point hitch type		Category II	Category II	Category II	Category II
@lift point	kg.f(lbs)	2075(4575)	2075(4575)	2256(4974)	2256(4974)
@24 in.behind lift point	kg.f(lbs)	1630(3594)	1630(3594)	1768(3898)	1768(3898)
No. of standard remote valve ports (Rear)		4	4	4	4
PTO					
Rear PTO Shaft		SAE 1-3/8, 6 Spline	SAE 1-3/8, 6 Spline	SAE 1-3/8, 6 Spline	SAE 1-3/8, 6 Spline
Type		Independent	Independent	Independent	Independent
Rated PTO rpm	rpm	540 / 540E	540 / 540E	540 / 540E	540 / 540E
Tire Size					
AG. Tire					
Front		11.2-20	11.2-20	280/85R24	280/85R24
Rear		14.9-30	14.9-30	420/85R30	420/85R30
Traveling Speeds					
Forward	km/h(mph)	0.16 ~ 36.83 (0.1 ~ 22.88)	0.16 ~ 36.83 (0.1 ~ 22.88)	0.17 ~ 37.66 (0.1 ~ 23.4)	0.17 ~ 37.66 (0.1 ~ 23.4)
Reverse	km/h(mph)	0.16 ~ 36.21 (0.1 ~ 22.5)	0.16 ~ 36.21 (0.1 ~ 22.5)	0.17 ~ 37.03 (0.1 ~ 23.01)	0.17 ~ 37.03 (0.1 ~ 23.01)
Dimensions					
Overall length (w/o front weight and w/3pt hitch)	mm(in.)	3685	3685	3715	3715
Overall width (minimum tread)	mm(in.)	1800	1800	1960	1960
Overall height (ROPS)	mm(in.)	2700	NA	2730	NA
Overall height (CAB)	mm(in.)	NA	2630	NA	2655
Wheel base	mm(in.)	2100	2100	2130	2130
Ground(Crop) clearance	mm(in.)	420	420	440	440
Weight with ROPS	kg.f(lbs)	2360	NA	2540	NA
Weight with Cabin and AG tires	kg.f(lbs)	NA	2630	NA	2795

-NOTE : The specification are subject to change for the purpose of improvement without any notice.

STANDARD EQUIPMENT

- Joystick

Auto PTO

Parking Brake

7pin socket

Remote valve (2set)
- Sunvisor (Cab only)

CD Player (Cab only)

Heater/Air conditioner

Drawbar

ROPS

OPTIONAL EQUIPMENT

- Tilt Steering wheel

Auto 4WD

Rear view mirror

Power socket
- Front weight

Sun canopy