

CROSS HP

Cultivator for simplified tillage



CROSS HP 6

STANDARD EQUIPMENT

- » semi-mounted axle 965/ø36 mm
- » 4 rows of CX tines with spring protection and undercut width 370 mm
- » external CX tines with raking mouldboards
- » ø460 mm disc harrow (type A) with triangular rubber shock-absorber and bolt adjustment of working depth, replaceable, maintenance-free hub
- » ø600 mm pipe roller
- » hydraulic adjustment of working depth
- » frame hydraulically folded for transport with the help of 4 cylinders
- » chassis with wheels 500/45-22,5 and drawbar 2800 mm
- » front support wheels (340/55-16)


MODEL	4	5	6
CROSS HP			

ACCESSORIES AT EXTRA CHARGE

surcharge for a set of tines with narrow coulter			
surcharge for air brakes			
surcharge for hydraulic brakes			
hydraulic adjustment of the front wheels	—		
surcharge for hitch, ø40 mm *			
surcharge for hitch, ø50 mm *			
warning plates kit			
warning plates kit with lamps			
rollers acc. to table ROLLER LIST (page 45–47)			



Harrow A



Tine CX



Tine with narrow coulter

CROSS HP	4	5	6
Weight with ø600 mm pipe roller [kg]	6 300	6 950	7 270
Power demand [HP]	180 ÷ 240	240 ÷ 280	280 ÷ 320
No. of tines [pc.]	13	17	19
Tines spacing in the machine [mm]	300	290	305
Underbeam clearance [cm]	850	850	850
Beam spacing [cm]	750	750	750
Length of the machine [cm]	760	760	760

CROSS HP:

- » CX tine working depth: with undercutter: 15 cm without undercutter: 30 cm
- » load per tine: 550 kg
- » tines spacing: 30 cm