

SOLIS EVERYDAY

N90



90HP ROPS

ENGINE

ITL 4105 ELT Diesel Engine
Water Cooled
4Cylinder/4087cc Turbocharged Intercooled
90 Hp @ 2200 RPM
360Nm Max Torque @1300 RPM
Dual dry air cleaner with clogging sensor
Upswept exhaust with silencer under hood
73 Lt fuel tank capacity

TRANSMISSION

Carraro Synchronised Shuttle Transmission
12 Forward gears + 12 Reverse gears
Forward/Reverse LH Shuttle lever
Double dry clutch
30 km/h Gearbox
4WD Mode - Mechanical lever engagement
Carraro Narrow Front Axle
Front Axle Power steering
Rear Diff Lock - Mechanical foot pedal
Rear oil immersed brakes
Mechanical hand brake

PTO

2 Speed Rear PTO
540 + 540 Economy Speed
540 @ 1938 engine rpm
540E @ 1648 engine rpm
Mechanical lever engagement
Mechanical selector lever

OPERATING AREA

N Type Operating area
Foldable front mounted 2 Post ROPS
Rubber floor mat
Front noise/mud deflectors
Adjustable mechanical suspended seat
Seat equipped with seatbelt
Analogue dash with digital hour meter
Ergonomic controls

ELECTRICAL

12V -85Ah Battery
12V - 90 Amp Alternator
Battery isolator switch
2 Bonnet headlights with Hi/lo beam
Rear work light
Front park lights
Front and rear indicators
Rear brake and tail lights
Rotary Beacon
7 Pin trailer socket

HYDRAULICS/3-POINT LINKAGE/HITCH

Open Centre Hydraulics
Hydraulic Pump Capacity - 45 LPM
Rear remotes - 2 sets Single/Double Acting
CAT 2 Rear 3-point linkage
RH Position and Draft Levers
CAT 2 Ball ends
2500kg capacity
Adjustable sway bars
Swinging rear drawbar

WHEELS/DIMENSIONS/WEIGHTS

Radial Ag tyre and wheel package
280/70R18 Front tyres
360/70R28 Rear tyres
Front dynamic steering fenders
Front weight package -258kg
Rear wheel weights - 2 x 30kg
Wheelbase - 2216 mm
Total length -TBC
Total width - TBC
Total height - TBC
Min ground clearance - TBC
Front track -TBC
Rear track -TBC
Tractor weight -2735kg

